

ARCA 403021



Sample image

Order symbol : ARCA 403021

Product nr : 8120007

UL Code : UL508A

Description : Cabinet, PC


Remarks : Grey cover, 2-point locking, hinges on the long side

EAN : 6418074079183

El. number :

- Finland : 3423054
- Denmark : 8212091058
- Sweden : 2500114

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions :	Height	Width	Depth
mm :	400	300	210

Accessories :
DRS ARCA DIN rail frame set

inch : 11.81 15.75 8.27

Materials :

Material : Polycarbonate
Base colour : RAL_7035
Cover colour : RAL 7035 -light grey
Gasket material : Polyurethane

Temperatures :

Temperature °C (short term) : -40 ... 120
Temperature °C (continuous) : -40 ... 80
Temperature °F (short term) : -40 ... 250
Temperature °F (continuous) : -40 ... 175

403021 (385 x 285 x 35)
SBK ARCA 30 Support bar kit (235 x 40 x 30)
RCS ARCA 4030 Rain canopy set for size 4030
SBK ARCA 40 Support bar kit (340 x 40 x 30)
IDS ARCA 4030 Inner door set (385 x 285 x 35)
PMK ARCA 30 PoleMounting kit, for pole ø100-300mm (385 x 285 x 35)
DSP ARCA VLS Door stopper ARCA, vertical, left, small
MPMP ARCA 4030 Mounting plate multiperforated (350x250x2 mm - ø3.6 mm)
DSP ARCA VRS Door stopper ARCA, vertical, right, small
MPS ARCA 4030 Mounting plate (350x250x2 mm) (350 x 250 x 2)
MPP ARCA 4030 Mounting plate perforated (350x250x2 mm - 26x11 mm) (350 x 250 x 2)
MPX ARCA 4030 Mounting plate (350x250 mm) (350 x 250 x 15)

Ratings :

Ingress protection (EN 60529): IP66;
Impact Resistance (EN 62262): IK10;
electrical_insulation : Totally insulated
Halogen free (DIN/VDE 0472, Part 815) : Yes
UV resistance : UL 508
Flammability Rating : UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C : 960C
NEMA Class NEMA__1_4_4X_12_13

Certificates :

Certificate FI 40467